



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/720,701	11/24/2003	Jeong-Woo Jwa	038779/271570	5383
826	7590	09/10/2007		
ALSTON & BIRD LLP BANK OF AMERICA PLAZA 101 SOUTH TRYON STREET, SUITE 4000 CHARLOTTE, NC 28280-4000			EXAMINER KOLETOWO, RASHEEDAT	
			ART UNIT 2609	PAPER NUMBER
			MAIL DATE 09/10/2007	DELIVERY MODE PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

## Office Action Summary

**Application No.**

10/720,701

**Applicant(s)**

JWA, JEONG-WOO

**Examiner**

Rasheedat O. Koletowo

**Art Unit**

2609

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☐ Responsive to communication(s) filed on 24 November 2003.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 1-7 and 13-16 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-7 and 13-16 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
- Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
- Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☒ Some \* c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
  - ☒ Certified copies of the priority documents have been received in Application No. 10-2003-0019201.
  - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- ☒ Notice of References Cited (PTO-892)
- ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- ☐ Information Disclosure Statement(s) (PTO/SB/08)  
Paper No(s)/Mail Date \_\_\_\_\_
- ☐ Interview Summary (PTO-413)  
Paper No(s)/Mail Date. \_\_\_\_\_
- ☐ Notice of Informal Patent Application
- ☐ Other: \_\_\_\_\_

### **DETAILED ACTION**

This is in response to the application filed on November 24<sup>th</sup>, 2003, where applicant has filed application No. 10/720,701. The following Office Action is based on the application filed on November 24<sup>th</sup>, 2003 in which claims 1-7, 13-16 and figure 1 are elected.

### ***Election/Restrictions***

Claims 8-12 and 17-24 are withdrawn from further consideration pursuant to 37 CFR 1.142(b) as being drawn to a nonelected invention, there being no allowable generic or linking claim. Election was made **with** traverse in the reply filed on July 30, 2007.

### ***Priority***

Receipt is acknowledged of papers submitted under 35 U.S.C. 119(a)-(d), which papers have been placed of record in the file.

### ***Information Disclosure Statement***

The information disclosure statement filed November 24, 2003 complies with 37 CFR 1.97(d) because it lacks a statement as specified in 37 CFR 1.97(e). It has been placed in the application file, but the information referred to therein has not been considered.

***Status of Claims***

Applicant has elected claims 1-7 and 13-16 drawn on the first species of Figure 1.

Claims 1-7 and 13-16 are pending, of which claims 1 and 13 are in independent form.

***Claim Rejections - 35 USC § 112***

The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter, which the applicant regards as his invention.

Claim 7 is objected to because of the phase “(preferably M)” renders the claim indefinite. It is unclear as to whether or not the limitation(s) following the phase is bound by a maximum number of units for performing IDFT on the converted information.

***Claim Rejections - 35 USC § 102***

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

**Claims 1, 2 and 7 are rejected under 35 U.S.C. 102(e) as being anticipated by Ikeda (US 5,471,464), hereinafter Ikeda.**

Art Unit: 2609

Re claim 1, Ikeda (US 5,471,464) discloses in the summary of the invention, an OFDM wireless communication system comprising:

a transmitter for performing IDFT (inverse discrete Fourier transform) on an information transmit vector at least twice to modulate it into an OFDM (orthogonal frequency division multiplexing) signal **[a first IDFT means for performing IDFT on a first digital component signal to produce a first time signal and a second IDFT means for performing IDFT on a second digital component signal in an orthogonal relationship with the first digital signal to produce a second time signal, see col. 6, lines 47-65]**, transmitting the modulated OFDM signal through a multi-path fading channel, modulating a pilot symbol vector for predicting an amplitude and a phase of the multi-path fading channel into an OFDM signal **[the IDFT circuit is performed so that the frequency region I and Q channel signals are converted to time region signals, thereby making the IDFT coefficient corresponding to a predetermined carrier wave signal in the IDFT processing results a fixed value, see col. 17, lines 7-10]**, and transmitting the modulated OFDM signal through the multi-path fading channel **[the RF converter 318 converts the signal restricted in the bandpass filter to the transmission frequency and sends it out over the air as signal for the transmission antenna 319, see col.17, lines 5-54]**; and

a receiver for demodulating the pilot symbol vector received through the multi-path fading channel to predict the amplitude and the phase of the multi-path fading channel **[the tuner converts the received RF signal captured by the receiving antenna into a predetermined intermediate frequency signal, see**

**col. 18, lines 8-12]**, using the predicted amplitude and phase to compensate the amplitude and the phase multiplied to the received information transmit vector **[the low pass filters pass the predetermined frequency component signals in the base band converted in frequency by the multiplies and frequency components with higher outliers are removed, see col. 18 lines 63-67]**, performing DFT (discrete Fourier transform) on the compensated information transmit vector to average a noise signal value increased by the channel compensation in a specific interval with an amplitude of the channel with less than a mean value into a mean value within an OFDM symbol interval, and outputting the mean value **[the DFT circuit perform DFT processing on the digital signals output and converting the digital signals from the time region to the frequency region, see col. 19, lines 8-12]**.

Re claim 2, Ikeda (US 5,471,464) discloses of an OFDM wireless communication system of claim 1, wherein the transmitter comprises:

a mapper for mapping an externally received binary information sequence to symbols according to the MQAM (M-ary quadrature amplitude modulation) method **[the modulation method of changing both the phase and amplitude of a plurality of carrier waves signal known as QAM, see col.1, para10 and Fig 3 - synchronization symbol signal]**;

a first IDFT unit for performing IDFT on the converted information transmit vectors and a second IDFT unit for performing IDFT on the IDFT-performed signals to modulate them into OFDM signals **[a first IDFT means for performing IDFT on a first**

**digital component signal to produce a first time signal and a second IDFT means for performing IDFT on a second digital component signal in an orthogonal relationship with the first digital signal to produce a second time signal, see col. 6, lines 47-49];**

a serial to parallel converter for converting the mapped symbols into vector data that are information transmit vectors [see Fig 1 – S/P converter 861];

a third IDFT unit for modulating a pilot symbol vector for predicting the amplitude and phase of the multi-path fading channel into an OFDM signal [the IDFT circuit is performed so that the frequency region I and Q channel signals are converted to time region signals, thereby making the IDFT coefficient corresponding to a predetermined carrier wave signal in the IDFT processing results a fixed value, see col. 17, lines 3-10]; and

a parallel to serial converter and guard interval inserter for inserting a guard interval into the signal received from the second IDFT unit, converting the guard interval inserted information transmit vector into a serial signal and transmitting it, and converting the guard interval inserted pilot symbol vector into a serial signal and transmitting it [a first guard interval adding means provided after first IDFT means and the second guard interval adds second time region signal after IDFT means, see col. 7, lines 18-24 and Fig 5 – P/S converters 304 and 305].

Art Unit: 2609

Re claim 7, Ikeda (US 5,471,464) discloses a wireless communication system including a transmitter for transmitting data using a multi-path fading channel and a receiver for receiving them from the transmitter, comprising:

a mapper for mapping an externally received binary information sequence to at least one symbol according to the MQAM (M-ary quadrature amplitude modulation) method **[a plurality of carrier wave signals N of the modulated signals and QAM modulation is performed on a plurality of symbols, see col. 10, lines 63-65];**

a serial to parallel converter for converting the mapped symbols into vector data which are information transmit vectors **[see Fig 1 – S/P converter 861];**

a first IDFT (inverse discrete Fourier transform) unit including at least one (preferably M) IDFT unit for performing IDFT on the converted information transmit vectors **[a first IDFT means for performing IDFT on a first digital component signal to produce a first time signal and a second IDFT means for performing IDFT on a second digital component signal in an orthogonal relationship with the first digital signal to produce a second time signal, see col. 6, col. 47-59];**

an interleaver for writing sub-channel values of the respective transmit vectors received from the IDFT unit in an MxN memory buffer in the first direction **[the converters converts the IDFT circuit to P/S to the buffer memories. The buffer memories 306 and 307 perform processing such as adding guard**



Art Unit: 2609

**intervals to the signals input from the P/S converters and outputs the same to the D/A converters, see col.17, lines 18-22];**

a second IDFT unit including at least one (preferably M) IDFT unit for reading the sub-channel values written in the first direction in the second direction when the writing in the first direction is finished, performing IDFT on the read sub-channel values, and modulating them to OFDM (orthogonal frequency division multiplexing) signals **[a first IDFT means for performing IDFT on a first digital component signal to produce a first time signal and a second IDFT means for performing IDFT on a second digital component signal in an orthogonal relationship with the first digital signal to produce a second time signal, see col. 6, col. 50-64];**

a third IDFT unit for modulating a pilot symbol vector for predicting an amplitude and a phase of the multi-path fading channel to an OFDM signal **[the IDFT circuit is performed so that the frequency region I and Q channel signals are converted to time region signals, thereby making the IDFT coefficient corresponding to a predetermined carrier wave signal in the IDFT processing results a fixed value, see col. 17, lines 3-10]; and**

a parallel to serial converter and guard interval inserter for inserting a guard interval into the signal received from the second IDFT unit, converting the guard interval inserted information transmit vector into a serial signal, transmitting the serial signal, converting the guard interval inserted pilot symbol

Art Unit: 2609

vector into a serial signal, and transmitting it to the transmitter **[a first guard interval adding means provided after first IDFT means and the second guard interval adds second time region signal after IDFT means, col. 7, lines 18-24 and Fig 5 – P/S converters 304 and 305]**.

**Claims 13-16 are rejected under 35 U.S.C. 102(e) as being anticipated by Zhang (2005/0276254 A1), hereinafter Zhang.**

Re claim 13, **Zhang (2005/0276254 A1)** teaches of a method for compensating a channel in a wireless communication system for transmitting and receiving data using a multi-path fading channel, comprising:

(a) performing IDFT (inverse discrete Fourier transform) on a vector for information transmission to modulate the vector into an OFDM (orthogonal frequency division multiplexing) signal, and transmitting the modulated signal through the multi-path fading channel **[a pilot symbol is inserted into the converter to produce a total of M symbols; these data sequences are fed into an inverse Fourier transform from a mapping process; the signals are up-converted to a carrier frequency and transmitted over air-link, see pp3, para27]**;

(b) modulating a pilot symbol vector for predicting an amplitude and a phase of the multi-path fading channel into an OFDM signal, and transmitting the modulated signal through the multi-path fading channel **[sub-channels may be**

**used to transmit pilot signals wherein the pilot symbol is used to estimate the fading channel properties which corrupt the transmitted signal, see pp1, para7];**

(c) demodulating the pilot symbol vector received through the multi-path fading channel to predict the amplitude and the phase of the multi-path fading channel **[for transmission channels with significant noise, channel compensation must be performed in each data block with the pilot symbols inserted in the given data block, see pp1, para7];**

(d) compensating the amplitude and the phase of the channel multiplied to the received information transmit vector by using the predicted amplitude and the phase of the channel **[a pilot-based signal correction is performed using a channel estimation process and a signal correction process, see pp5, para28, lines 11-12]; and**

(e) performing DFT on the compensated channel signal, averaging a noise signal value enhanced by the channel compensation in a specific interval with an amplitude of the channel with less than a mean value into a mean value within an OFDM symbol interval, and outputting the mean value **[using one or more phase differences to generate an average phase difference, wherein determining the residual phases error is based on average phase differences and correcting phases of channel compensated data symbols is based on the determined residual phase error, see pp1, para11].**

Re claim 14, **Zhang (2005/0276254 A1)** discloses a method of claim 13, wherein (e)

Art Unit: 2609

comprises using the MMSE (minimum mean square error) equalization method to compensate the amplitude and the phase of the channel multiplied to the received transmit vector **[the residual phase error in each element in of the signal vector is removed (MSE) by multiplying the received signal with the estimated gain error, see pp7, para86].**

Re claim 15, **Zhang (2005/0276254 A1)** discloses of the method of claim 13, wherein (e) comprises using the ZF (zero forcing) equalization method to compensate the amplitude and the phase of the channel multiplied to the received transmit vector **[if the channel estimation error is small that the OFDM block signal is in deep fading, the channel gain is almost zero, therefore the noise will be obtained only from the channel estimation and signal correction, see pp 5, para54].**

Re claim 16, **Zhang (2005/0276254 A1)** discloses of the method of claim 13, wherein (e) comprises using the gain limit equalization method to compensate the amplitude and the phase of the channel multiplied to the received transmit vector **[to reduce the residual phase error in the received constellation signals due to the pilot-based channel estimation, the estimation error is first calculated then removed from the received signals, see pp5, para56].**

***Claim Rejections - 35 USC § 103***

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

**Claims 3-6 are rejected under 35 U.S.C. 103(a) as being unpatentable over Ikeda (US 5,471,464) in view Zhang (2005/0276254 A1).**

Re claims 3, **Ikeda (US 5,471,464)** discloses of the OFDM wireless communication system of claim 2, wherein the receiver comprises:

a guard interval eliminator and serial to parallel converter for eliminating the guard interval from the converted and received serial signal, and converting the guard interval eliminated serial signal into an information transmit vector and a pilot symbol vector respectively [**both orthogonal signals converted to serial signals in the P/S converters are processed to remove the guard intervals added at the time of modulation and are outputted orthogonally as digital format I and Q channel signals, see para40**];

a first DFT unit for demodulating the converted information transmit vector into an OFDM signal [a first DFT for performing DFT on the extracted first component signal using a first time window signal to generate a first frequency region component, see para97];

Art Unit: 2609

a third DFT unit for demodulating the converted pilot symbol vector into an OFDM signal **[the DFT time window is synchronized, output is based on outputs of the converters for accurate phase, see col. 19, lines 60-65];**

a channel predictor and interpolator for predicting the amplitude and phase of the multi-path fading channel using the demodulated pilot symbol vector **[the amplitude comparison circuits compares squared values with the reference value REF output from the reference value; when the square value is lower than the reference, the symbol is detected as 1, see col. 5, lines 5-9];**

a parallel to serial converter for converting the signal received from the second DFT unit into a serial signal **[Fig.7 – P/S converter 122];** and

a decoder for restoring the converted serial signal into a binary information sequence, and outputting the binary information sequence **[the multiplexer selects and outputs decode value from the decoder 1285 for adjusting the phase of the DFT time window based on the level of the output signal, see col. 22, lines 48-52].**

However, Ikeda (US 5,471,464) fails to explicitly disclose a channel compensator for compensating the amplitude and phase of the channel multiplied to the demodulated information transmit vector according to the predicted amplitude and phase of the channel. Zhang (2005/0276254 A1) nevertheless, teaches of **[the signal vector is corrected by removing the residual phase error in each element of the signal vector by multiplying the received signal with the estimated residual phase error, see para86, and steps 706 and 722 of the channel compensator in Fig 7].** At the

Art Unit: 2609

time the invention was made, it would have been obvious to a person skilled in the art to modify the teachings of Ikeda (US 5,471,464) wherein, the phase error output being filtered by the low pass filter incorporates Zhang's receiver processing unit 500 to remove the largest maximum magnitude phase error as described in the removal process. The motivation being to demodulate the OFDM signals by correctly reproducing the carrier wave signals to generate the DFT phase used in the DFT processing.

Additionally, Ikeda (US 5,471,464) fails to explicitly disclose a second DFT unit for performing DFT on the compensated channel signal, and averaging a noise signal value which becomes enhanced in a specific interval with an amplitude of the channel with less than a mean value, to a mean value within a symbol interval **[the channel estimate is first compensated with the estimated residual phase error and then corrected channel estimate is used to correct the received signal vector. Next the phase differences are averaged, see para86-87, and step 718 of the channel compensator in Fig 7]**. At the time of invention, it would have be obvious to a person skilled in the art to modify the teachings of Ikeda to incorporate the averaging process 518 as taught by Zhang in the synchronization unit to achieve a synchronized phase signal for the DFT time window. One of skilled in the art would have been motivated to remove the guard interval from received signals by correcting the output of the DFT time window for phase errors to span a predetermined frequency.

Re claim 4, Ikeda (US 5,471,464) discloses a system meeting all preceding limitations

Art Unit: 2609

of the parent claim, however fails to disclose the OFDM wireless communication system of claim 2, wherein the channel compensator compensates the amplitude and phase of the channel through the MMSE (minimum mean square error) equalization method using the predicted amplitude and phase of the channel. Conversely, **Zhang (2005/0276254 A1)** teaches of channel estimation for compensation purposes. The method of estimation as computed in equations 9-17 is based on a previously known pilot symbol and a received pilot symbol. The channel gain error is based on the AWGN and ICI interferences and the phase error is based on the gain. Thus, for one of ordinary skill in the art, it would have been obvious to derive from Zhang's linear equalization solution obtained using the MMSE optimization to perform variant calculations on concepts (phase, amplitude) to yield essentially similar and predictable results.

Re claim 5, **Ikeda (US 5,471,464)** discloses a system meeting all preceding limitations of the parent claim, however fails to disclose the OFDM wireless communication system of claim 4, wherein the channel compensator compensates the amplitude and phase of the channel through the ZF (zero forcing) equalization method using the predicted amplitude and phase of the channel. However **Zhang (2005/0276254 A1)** teaches of channel estimation for in Equations 20 and 21 where by the estimated error (channel gain) for an individual symbol is reduced to equation 21 if error is very small or zero. Therefore, for one of ordinary skill in the art, it would have been obvious to remove substantially minute error gain factors such as the channel estimator and angle



Art Unit: 2609

residuals estimation in order to prevent degradation in the MMSE optimization.

Re claim 6, **Ikeda (US 5,471,464)** discloses a system meeting all preceding limitations of the parent claim, however fails to disclose the OFDM wireless communication system of claim 4, wherein the channel compensator compensates the amplitude and phase of the channel through a gain limit equalization method using the predicted amplitude and phase of the channel. However **Zhang (2005/0276254 A1)** teaches in Equations 22 and 23 of residual phase error estimation used for correcting received signals based on pilot based estimations. For one of ordinary skill in the art, it would have been obvious to first calculate the channel phase estimation error (gain), and then remove the calculated gain estimation factor from the overall estimation once it has been used to estimate the gain on the received signal. Therefore, the motivation to derive from Zhang's linear equalization solution would be to reduce the effect of the error estimator on the received signal by preventing degradation in the MMSE optimization.

### ***Conclusion***

The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

Hadad (US 2005/0207334 A1) discloses an OFDM communication channel. The information regarding the pilot extraction and analysis unit in Fig. 5 is relevant material.

Taura et al. (US 6,028,900) discloses a digital broadcast receiver. The information regarding the compensation method and the DFT processor unit are of relevance.

Kim et al. (US 2004/0042385 A1) discloses a frequency offset estimator and a channel equalization method. Equation 4 and information regarding channel compensation using zero forcing are relevant material.

Eidson. (US 2004/0047284 A1) discloses a transmit framing structure for multi-path channels. Information regarding channel estimation using MMSE and equalization and equations 13 and 17 are relevant material

Fujii (US 2005/0163238 A1) discloses transceiver method and system. The multi-carrier CDMA scheme is of relevance.

Sim (US 7,068,981 B2) discloses a method for transmitting signal in a mobile communication system. The vector estimation unit of the receiving end is of relevance.

Nakahara et al. (US 2006/0104195 A1) discloses an OFDM transmission method and system. The first, second reference pilot and symbol generator are relevant material.

Art Unit: 2609

Yoshida et al. (US 2003/0053412 A1) discloses an OFDM receiving method and system. The calculation unit disclosed in Fig 21 is of relevance.

Sudo (US 2003/0012126 A1) discloses an OFDM communication method and system. The selection section unit is relevant material.

Park et al. (US 2007/0157058 A1) discloses a delay fault test controller. The update operation and capture operation in Fig. 5 are relevant material.

### ***Contacts***

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Rasheedat O. Koletowo whose telephone number is 571-272-9824. The examiner can normally be reached on Monday-Thursday, 7:30am-5pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Frantz Coby can be reached on 571-272-4017. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2609

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Rasheedat Koletowo  
R.K./r.k.



August 23<sup>rd</sup>, 2007



FRANTZ COBY  
SUPERVISORY PATENT EXAMINER